

## 2-Piece Domestic Stainless Steel Ball Valves

### Feature


- Blow-out proof stem

### Materials

- 316 stainless ball and stem
- RPTFE seal
- Vinyl handle cover

### Specifications

- Temperature range: **-40°F to 400°F (-40°C to 204°C)**
- Pressure rating: **1,000 PSI CWP**
- Pressure rating: **150 PSI saturated steam**
- Vacuum service to 29 inches Hg



Female NPT	Port	316 Stainless Steel Part #
1/4"	full	DSBV25
3/8"		DSBV38
1/2"		DSBV50
3/4"		DSBV75
1"		DSBV100
1-1/4"		DSBV125
1-1/2"		DSBV150
2"		DSBV200

## Stainless Steel Ball Valves Full Port

### Applications

- For use with water, oil, and gas

### Feature

- Blow-out proof stem design

### Materials

- 316 stainless steel ball and stem
- RPTFE seat, joint gasket, and thrust washer

### Specifications

- Temperature range: **-20°F to 300°F (-29°C to 149°C)** as long as the valve is run fully open/closed
- Pressure rating:
  - 1/4" - 2" rated to **1000 PSI WOG (CWP)**
  - 2-1/2" - 3" rated to **800 PSI WOG (CWP)**
  - 100 PSI saturated steam**



Female NPT	Port	316 Stainless Steel Part #
1/4"	full	SSBV25
3/8"		SSBV38
1/2"		SSBV50
3/4"		SSBV75
1"		SSBV100
1-1/4"		SSBV125
1-1/2"		SSBV150
2"		SSBV200
2-1/2"		SSBV250
3"		SSBV300