

## 500# All Polyester Rack Hose - Aluminum Couplings UL Labeled


**Application:**

- for pin rack service / emergency fire fighting only, not to be used for washdown



**Features:**

- outer construction: single jacket, all polyester
- tube construction: clear thermoplastic
- proof pressure: **300 PSI** at ambient temperature (70°F)
- service test pressure: **150 PSI** at ambient temperature (70°F)
- working pressure: **135 PSI** at ambient temperature (70°F)
- Underwriters Listed



folded



coiled

**Coupled with female and male aluminum rocker lug expansion ring couplings**

Size	Length	Thread	Folded Part #	Price	Coiled Part #	Price
1½"	50'	NST (NH)	<b>R515U50RAF/F</b>	<b>\$246.65</b>	<b>R515U50RAF</b>	<b>\$246.65</b>
1½"	50'	NPSH	<b>R515U50RAS/F</b>	<b>246.65</b>	<b>R515U50RAS</b>	<b>246.65</b>
1½"	100'	NST (NH)	<b>R515U100RAF/F</b>	<b>442.45</b>	<b>R515U100RAF</b>	<b>442.45</b>
1½"	100'	NPSH	<b>R515U100RAS/F</b>	<b>442.45</b>	<b>R515U100RAS</b>	<b>442.45</b>

## 500# All Polyester Rack Hose - Aluminum Couplings non-UL Labeled


**Application:**

- for pin rack service / emergency fire fighting only, not to be used for washdown



**Features:**

- outer construction: single jacket, all polyester
- tube construction: clear thermoplastic
- proof pressure: **500 PSI**
- service test pressure: **250 PSI** at ambient temperature (70°F)
- working pressure: **225 PSI** at ambient temperature (70°F)



folded



coiled

**Coupled with female and male aluminum rocker lug expansion ring couplings**

Size	Length	Thread	Folded Part #	Price	Coiled Part #	Price
1½"	50'	NST (NH)	<b>R515-50RAF/F</b>	<b>\$217.35</b>	<b>R515-50RAF</b>	<b>\$217.35</b>
1½"	50'	NPSH	<b>R515-50RAS/F</b>	<b>217.35</b>	<b>R515-50RAS</b>	<b>217.35</b>
1½"	100'	NST (NH)	<b>R515100RAF/F</b>	<b>342.80</b>	<b>R515100RAF</b>	<b>342.80</b>
1½"	100'	NPSH	<b>R515100RAS/F</b>	<b>342.80</b>	<b>R515100RAS</b>	<b>342.80</b>

