


3000 Series Hydraulic Thread-to-Connect Couplings

Applications:

- Designed for extreme high pressure applications including hydraulic rams and pumps where low flow and pressures up to 10,000 PSI are encountered.

Features:

- interchangeable with Parker 3000, Bruning IP 370 and Enerpac C 604, see Hydraulic Profile Chart on page 849
- polyurethane seals
- ball type check valves are in both the couplers and plugs




Male Couplers

Size	Male NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Pkg Qty
1/4"	1/4" - 18	10,000	steel	30-200	\$43.00	5
3/8"	3/8" - 18	10,000	steel	30-300	45.00	5



Female Couplers

Size	Female NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Pkg Qty
3/8"	3/8" - 18	10,000	steel	30-300F	\$50.00	5



Plugs

Size	Female NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Pkg Qty
1/4"	1/4" - 18	10,000	steel	31-200	\$25.50	5
3/8"	3/8" - 18	10,000	steel	31-300	26.00	5

Screw Type Dust Plugs



Body Size	Material	Part #	Price/E	Opt Qty
1/4"	steel	30-200DP	\$11.20	5
3/8"	steel	30-300DP	10.70	5

Screw Type Dust Caps



Body Size	Material	Part #	Price/E	Pkg Qty
1/4"	steel	31-200DC	\$11.80	5
3/8"	steel	31-300DC	13.60	5