

Adjustable Pressure Restricting Device

Features:

- for installation on Class I or Class III standpipe system hose outlets
- device restricts pressure in the piping system to such a degree that hose lines can be handled by persons untrained in the handling of heavy fire streams
- New York City Board of Standards and Appeals, approval # MEA 54-07-E
- 2½" U/L listed
- working pressure: **175 PSI** at 70°F (21°C)



Female Thread	Male Thread	Cast Brass Part #	Price/E
1½" NST (NH)	1½" NST (NH)	APRD150F	\$350.00
2½" NST (NH)	2½" NST (NH)	APRD250F	397.00
2½" NYC	2½" NYC	APRD250NYC	397.00



Domestic Cast Angle Hose Valves



Features:

- U/L listed and FM approved
- aluminum hand wheel
- working pressure: **300 PSI** at 70°F (21°C)

Inlet Female NPT	Outlet Male Thread	Cast Brass Part #	Price/E
1½"	1½" NST (NH)	AV150	\$300.00
	1½" NYFD	AV150NYFD¹	330.00
	1½" NPSH	AV150S	316.75
	1½" NPT	AV150T	331.45
2½"	2½" NST (NH)	AV250	473.65
	2½" NYC	AV250NYC¹	473.65
	2½" NYFD	AV250NYFD¹	473.65
	2½" NPSH	AV250S	473.65

¹ supplied with red hand wheel



Inlet Female NPT	Outlet Female NPT	Cast Brass Part #	Price/E
1½"	1½"	AVF150	\$300.00
2½"	2½"	AVF250	473.65

Replacement Parts

Description	Part #	Price/E
aluminum handwheel for 1½" valve	AV150-W	\$17.45
aluminum handwheel for 2½" valve	AV250-W	26.00
handwheel nut for 1½" valve	AV150-N	1.55
handwheel nut for 2½" valve	AV250-N	1.50
valve seal rubber for 1½" valve	AV150-RBR	17.80
valve seal rubber for 2½" valve	AV250-RBR	18.70

Dimensions

Size	A	B	C closed	C open	D	F
1½"	2-11/64"	2-7/32"	6-5/8"	7-21/32"	3-3/4"	2-13/16"
2½"	3-3/16"	3-3/16"	9-1/4"	11"	5"	3-19/32"

