

Tube Hex Hangers


Hex Hanger with Rubber Grommets and 3/8" NPT - B24RGC

Features

- Coupler is all thread 3/8"-16
- Optional: 1/2"-13 all thread or 3/8"-16 all thread

Specification

- Rubber grommets maximum temperature: 257°F (125°C)



M

3/8" NPT

Tube O.D.	A (in)	B (in)	C (in)	Grommet Qty	304 Stainless Steel Part #
1/2" - 3/4"	3.43	1.45	0.75	3	B24RGC-G75
1"	3.43	1.45	0.75	3	B24RGC-G100
1-1/2"	4.00	2.13	0.75	3	B24RGC-G150
2"	4.50	2.50	0.75	3	B24RGC-G200
2-1/2"	4.75	1.13	0.75	3	B24RGC-G250
3"	5.50	3.75	0.75	3	B24RGC-G300
4"	6.75	4.75	0.75	4	B24RGC-G400
6"	9.25	6.63	0.75	5	B24RGC-G600
8"	11.50	8.63	0.75	5	B24RGC-G800

3/8"-16

Tube O.D.	A (in)	B (in)	C (in)	Grommet Qty	304 Stainless Steel Part #
1/2" - 3/4"	3.43	1.45	0.75	3	B24RGC16-G75
1"	3.43	1.45	0.75	3	B24RGC16-G100
1-1/2"	4.00	2.13	0.75	3	B24RGC16-G150
2"	4.50	2.50	0.75	3	B24RGC16-G200
2-1/2"	4.75	1.13	0.75	3	B24RGC16-G250
3"	5.50	3.75	0.75	3	B24RGC16-G300
4"	6.75	4.75	0.75	4	B24RGC16-G400
6"	9.25	6.63	0.75	5	B24RGC16-G600
8"	11.50	8.63	0.75	5	B24RGC16-G800

1/2"-13

Tube O.D.	A (in)	B (in)	C (in)	Grommet Qty	304 Stainless Steel Part #
1/2" - 3/4"	3.43	1.45	0.75	3	B24RGC13-G75
1"	3.43	1.45	0.75	3	B24RGC13-G100
1-1/2"	4.00	2.13	0.75	3	B24RGC13-G150
2"	4.50	2.50	0.75	3	B24RGC13-G200
2-1/2"	4.75	1.13	0.75	3	B24RGC13-G250
3"	5.50	3.75	0.75	3	B24RGC13-G300
4"	6.75	4.75	0.75	4	B24RGC13-G400
6"	9.25	6.63	0.75	5	B24RGC13-G600
8"	11.50	8.63	0.75	5	B24RGC13-G800